



QUALICA-RD
5000



Satisfaction

High Technology Modular

CHANGEABLE FEEDERS OF 500 CARDS. SCRATCH FREE SYSTEM (IT DOESN'T SCRATCH THE CARDS).
CARD JUMP FREE SYSTEM (IT REDUCES THE CARD JUMPS). LOW PRINTING COST. BIG RANGE OF RIBBONS.
UV INK. LAMINATION WITH HOLOGRAMS (OPTIONAL). SATISFACTION!!.

The most modular industrial printer of the market.
Mifare, chip, magnetic stripe & lamination station modules available.
Ethernet included. UV ink.

www.qualicard.eu



RD 5000

Satisfaction...

Print type	Dye-Sublimation & Thermal transfer
Print Area	Edge to edge
Resolution	300 dpi
Double side printing	Optional
Lamination station	Optional
Feede	Automatic
Card size	ISO CR-80 (54 x 86 / 2.12" x 3.38")
Thickness	0.38 (15mil) ~ 1.2 (47mil)
Card Type	PVC, Composite PVC, PET
Print speed	
Monochrome	3,6 sec. (1000 cards / hour)
YMCKO	16 / 18 sec. (200 / 225 cards / hour)
YMCKOK	24 sec. (150 cards / hour)
Lamination Station (OPTIONAL)	
Lamination type	Single side/ Double side (it needs the flip over module)
Lamination film	0.6mil, 1.0mil (Clear & Holographic)
Laminating Speed	14 seg.
Capacity	500 Impresiones / Cinta
Cerradura Kensington	Si
Capacidad	
Input Hopper	500 cards
Output Hopper	100 cards, optional 500
System	
Memory	64M RAM
Display & Panel de control	LCD Display de 2 lines / 1 Led / 4 Buttons
Supported Platforms	Windows 2000 / 2003 / XP / Vista / 7 / 8 / MAC OS y LINUX
Communications	USB, Ethernet
Power supply	(AC 110 / 220V, 50 ~ 60Hz)
Voltage	24V / 2A
Temperature / Humidity	15 ~ 35°C / 35 ~ 70%
Dimensiones	
Dimensions	(W x L x H) 240mm x 214mm x 305mm
Weight	6,3 kg. / 13,9 lbs.
Optional encoders	
Magnetic	ISO-7811 (Pistas I - II - III Reader / Encoder) HiCo/LoCo, JIS II
Chip	ISO 7816 (ID-1)
Contactless (RFID)	MIFARE, ISO 14443 (TYPE A/B), ISO 15693
((Internal&External))	DESFIRE, iCLASS
Certifications	
	CE, UL, FCC, KCC
Warranty	
	3 years