

# QUALICA-RD TITAN PRINTER

## Retransfer Dual Card Printer

We will rock you...

- ✓ 600 dpi resolution, best printing quality
- ✓ Silver backgrounds, the only one
- ✓ Highest speed of the market
- ✓ No bending
- ✓ Less printing mistakes than anyone



3 years **warranty!**

**Qualica-RD TITAN** it is the only dual side printer in the market with silver panel to make incredible silver background prints.

**The fastest** and the only one that does not bend the cards even in single side print.

Extraordinary **robustness** that allows you to make large print runs without printing failures.



# Retransfer Identification Card Printer

QUALICA-RD Printing Software

## Features Qualica-RD TITAN

- Industrial & Commercial Grade Design.
- Over The Edge Full Card Printing.
- High Definition Printing.
- Large Card Feeder Capacity.
- Rapid Output / High Productivity.
- Supports Variety of Smart Card Encoders.
- Driver's License Cards, National ID Cards, Student ID Cards, Corporate ID Cards, Membership Card, All Kind of ID Cards.
- **Options:** RFID R/W, MSR R/W, SAM R/W.
- **Consumables:** YMCK, OVERLAY and YMCS. All 500 impressions  
Optional in projects: YMCKKK, YMCKS, YMCKF (400 impressions)
- **Cleaning set:** Cleaning Card, Cleaning Roller and Cleaning Swabs.



## Technical specifications

<b>Print Method</b>	Color retransfer technology
<b>Resolution</b>	600 DPI
<b>Print Capability</b>	Single Side, Double Side, Over-the-Edge, Photo quality
<b>Print Speed</b>	Single Side : 25 secs; Double Side : 55 secs
<b>Card Thickness</b>	0.5 - 1.0 mm thickness
<b>Security Features</b>	Own technology SOC, RFID ribbon, card feeder lock
<b>User Friendliness</b>	Easy to replace ribbons
<b>Card Loading</b>	Auto card feeder
<b>Operating Environment</b>	Temperature : 15 - 30°C; Humidity : 35 - 95%
<b>Storage Environment</b>	Temperature : 5 - 45°C; Humidity : 35 - 96%
<b>Dimensions</b>	12.25"(L) x 13.25"(W) x 17"(H)
<b>Weight</b>	22 kg (48 lbs)
<b>Warranty</b>	3 year Warranty
<b>Driver</b>	Windows 32 and 64 bit, Windows 7,8,10
<b>Power Supply</b>	Auto wide ranging 100-240V, 50/60 Hz
<b>Card Capacity</b>	Auto Feeder : 250 cards (0.76mm thickness); Manual Feed
<b>Cards Supported</b>	PVC, ABSS, PET, PET-G, PC; 85.6 x 53.98mm (ISO ID-1/CR-80 size)
<b>Interface</b>	USB 2.0, Ethernet 10/100 Duplex mode
<b>Certifications</b>	UL, FCC, CE, KCC and CCC