



3 years **warranty**



Biometrics



RFID



Barcode



QR Code

Qualica-RD **SPICA-405**

Half height steel turnstile for access control.

Qualica-RD SPICA-405. Bidirectional half-height turnstile, made of high quality brushed stainless steel. Suitable for both indoor and outdoor use. Complies with fire protection requirements.

Passage time limit (01-60 seconds), the passage time can be adjusted on the circuit board. It has a double bearing device, keeping the door in balance when facing an external force.

3 years warranty. Can be integrated with any kind of system (e.g. RFID device, fingerprint and biometric device).



SPICA-405 Half-Height Turnstile

Features

- The whole system operates smoothly, long-life performance, high reliability of operation and fast response.
- The mechanism is equipped with self-regulating hydraulic damper device.
- No noise and impact when running.
- Self-test function, when power on, automatic system restoration.
- Automatic reset function: when the half-height turnstile opens, but the passenger does not pass within a specific time (default 5s), the arm will automatically lock.



Technical specifications

| | |
|---------------------------|--|
| Material of the structure | 304 stainless steel |
| Dimensions | 1600 * 1500 * 990mm |
| Net Weight | 105kg / unit |
| Passage width | 560mm |
| Direction of passage | Unidirectional and Bidirectional |
| MCBF | 5 million |
| Power supply | AC220V/110V, 50/60Hz |
| Operating voltage | 24V DC |
| Power consumption | 40W |
| Operating temperature | -15 °C - 60 °C |
| Operating humidity | 0 ~ 95% (No freezing) |
| Operating environment | Indoor / Outdoor |
| Flow rate | 30 persons per minute |
| LED indicator | LED indicators on top and front |
| Input | Dry contact |
| Emergency | Automatic arm opening in case of power failure |
| Communication | RS485, TCP/IP (access control card required) |

Dimensions (mm)

